Material Safety Data Sheet

Date Prepared 3/2000

Product Number: 6320

Section 1: Manufacturer Identification

Mason Color Works, Inc.	Phone: (330) 385-4400
250 East 2 nd Street/P.O. Box 76	Fax: (330) 385-4488
East Liverpool, OH 43920-5076	

Section 2: Identification of Product

Chemical Family:	Inorganic
Product Names:	Delft Blue 6320
Chemical Abstract Number	er (CAS): 68186-86-7,18282-10-5
Chemical Name:	Cobalt Alumina Blue - Spinel
Chemical Formula:	$CoAl_2 O_4 + Zno.SiO_2 SnO_2$

Section 3 & Section 4: Hazardous ingredients Identity/Information and Overexposure Symptoms

	ACGIH-TLVs	OSHA PELs		NOISHA RELs
Alumina Oxide (Al_2O_3)	10 mg/mg^3 (total)	15 mg/m ³ (total)	N/A	
Cas # 1344-28-1		5 mg/m ³ (respirable)		

ACGIH: The value for particulate matter containing no asbestos and 1% crystalline silica.

Symptoms of overexposure:

Inhalation: Acute may cause coughing and shortness of breath. Chronic may adversely effect breathing capacity.
Eye Contact: Direct contact may cause irritation.
Skin Contact: May cause abrasions.
Ingestion: May cause irritation.

Cobalt Oxide (Co ₃ O ₄)	0.02 mg/m^3	0.5 mg/m^3	N/A
Cas # 1396-06-1			

ACGIH: Animal carcinogen: Agent is carcinogenic in experimental animals at dose levels, by route (s) of administration at site, or histologic type, or by mechanism considered relevant to workers exposure. Available epidemiologis studies do not confirm an increased risk of cancer in humans except under common levels of exposure.

Symptoms of Overexposure:

Inhalation: Prolonged inhalation of dust or metal dust, and fume or mist containing cobalt may cause serious respiratory illness. May cause an irritation of respiratory organs of sensitive persons resulting in obstruction of airways with shortness of breath.

Eye Contact: May cause serious eye irritation.

Skin Contact: Prolonged exposure may produce irritation.

Ingestion: Large amounts may cause irritation of the gastrointestinal tract, nausea, vomiting and diarrhea.

Silica, Crystalline (SiO ₂)	0.1 mg/m^3	10 mg/m^3	0.05 mg/m^3
Cas # 14808-60-7		$\overline{\text{SiO}_2 + 2}$	

Silica, Crystalline cont'd

Symptoms of overexposure:

Inhalation:

- a) Prolonged exposure to respirable crystalline silica (quartz) can cause Silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Silicosis increases risk of Tuberculosis.
- b) Inhaled from occupational sources is classified as carcinogenic to humans. (cancer)
- c) There is evidence that exposure to respirable crystalline silica or that the disease Silicosis is associated with increased incidence of Sceroderma, an auto-immune disorder manifested by fibrosis (scarring) of the skin and internal organs.
- d) There are several studies suggesting that exposure to respirable silica or that the disease Silicosis is associated with the increased incidence of kidney disorders. (Nephrotoxicity)

Eye Contact: May cause abrasions of the cornea.

Skin Contact: Not applicable.

Ingestion: Not applicable.

Tin Oxide (SnO)	2.0 mg/m^3	2.0 mg/m^3	2.0 mg/m^3
Cas # 21651-19-4			

Symptoms of overexposure:

Inhalation: No information found on acute overexposure. Chronic exposure to tin oxide fumes or dust may result in Stannosis, a form of Phenumoconiosis. **Eye Contact:** Abrasive, mild irritant

Skin Contact: Possible irritant.

Ingestion: Considered non-toxic.

Zinc Oxide (ZnO)	10 mg/m^3	10 mg/m ³ (Total)	5 mg/m^3
Cas # 1314-13-2		5 mg/m ³ (Respirable)	

Symptoms of overexposure:

Inhalation: High levels of dust may result in tightness of chest, metallic taste, cough, dizziness, fever, chills, headache, nausea, and dry throat. Chronic exposure may produce symptoms known as metal fume fever or "zinc shakes", an acute, self-limiting condition without recognized complications. Symptoms of metal fume fever include: chills, fever, muscular pain, nausea and vomiting. May aggravate respiratory conditions. **Eve Contact:** May cause irritation.

Eye Contact: May cause initiation.

Skin Contact: May cause irritation.

Ingestion: May cause irritation to the gastro-intestinal tract.

Section 5: Emergency and First Aid Procedures:

Eye: flush thoroughly with water for 15 minutes. Skin: remove contaminated clothing, wash thoroughly with soap and water. Inhalation: remove to fresh air, may give oxygen if needed. Ingestion: give large amounts of water to induce vomiting, only in conscious persons.

Principal Routes of Entry: Inhalation: Dust from this product may cause irritation of the respiratory system. Overexposure may cause lung damage. Ingestion: Large amounts may cause irritation of the gastrointestinal tract, nausea, vomiting and diarrhea. Skin & Eye: Nuisance dust, prolonged or repeated may cause irritation.

Section 6: Special Protection Information

Respiratory Protection:	Use only NIOSHA/OSHA approved respiratory protection with adequate ventilation; avoid breathing dust. Do not exceed Occupational Exposure Limits. Wash thoroughly after handling. No food or beverage should be consumed in work area.
Personal Protective Equip	: Wear appropriate gloves and goggles to avoid skin and eye contact. Safety
	showers and eye stations must be present in work stations.
Ventilation:	Use local exhaust or mechanical such as a dust collector to maintain dust levels
	below Occupational Exposure Limits.

Section 7: Physical and Chemical Characteristics

Boiling Point: N/A Solubility in water: trace Vapor Pressure (mmHg): N/A Vapor Density (air=1): N/A Appearance: blue powder Odor: oderless Specific Gravity (water=1): N/A Evaporation rate: None % Volatile by volume: None

Section 8: Reactivity Data

Stability: Stable Hazardous Polymerization: will not occur Incompatibility: None Hazard Decomposition of product: N/A

Section 9: Fire and Explosive Data

 Flash point: N/A
 Flammable Limits: None

 Unusual Fire and Explosion Hazard: None expected
 Extinguishing Media: Carbon dioxide, dry chemical or water

 Special Fire Fighting Procedures: Wear self contained breathing apparatus when large quantities involved.

Section 10: Spill or Leak Procedures:

Contain spillage and scoop or vaccum. Avoid making dust, put in appropriate container for disposal. Waste disposal method in accordance with Federal, State and Local Laws.

This product is a blend of various metal oxides, salts and some compounds which are interfused by high calcination to form the finished product. Section III, Hazardous Ingredients Identity/Information, and Section IV, Symptoms of Overexposure, pertain to individual components. Section V through Section X are in reference to the finished product.

ALL retailers of this product are **REQUIRED** by law to supply their customers with a copy of this material safety data sheet with initial purchase.

***SARA 313

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (SARA) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CRF, Part 372.

The information contained in this Material Safety Data Sheet must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY ! MATERIAL SAFETY DATA SHEETS ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.

DISCLAMER

Mason Color Works, Inc. believes the information contained in this material safety data sheet is believed to be accurate and reliable as of the date of publication or revision but makes no warranty that it is. This information provided should be made available as required by the Federal OSHA Hazard Communication Standard 1910.1200 to ANYONE who handles, uses, stores, transports or will otherwise be exposed to this product. Mason Color Works, Inc. Accepts no Responsibility for the health or safety of any individual who misuses this product by not complying with manufacturer's instructions contained herein or additional /other measures that may be required under particular conditions.

Last issued: 11/97 Updated : 3/2000